BITUMINOUS SURFACE COURSE

BEDDING MATERIAL COMPACTED TO 95%

COMPACT EXISTING UBC TO 95% PRIOR TO PAVING NEW UBC COMPACTED TO 95% PRIME WITH SS-1 OR H-1

- 1. COMPACTED BEDDING MATERIAL SHALL NORMALLY CONSIST OF BEDDING SAND.
- 2. IF APPROVED BY CITY ENGINEER, 3/4" DRAIN ROCK MAY BE USED FOR BEDDING MATERIAL

SAW CUT BACK 12" MIN FROM TRENCH WALL AFTER TRENCH HAS BEEN BACKFILLED AND COMPACTED. THEN INSTALL UBC / ASPHALT SECTION

> 3" MINIMUM OR MATCH EXISTING

- USE OF PEA GRAVEL OR COURSE SAND FOR BEDDING MATERIAL IS PROHIBITED UNLESS
- USE OF NATIVE MATERIAL FOR BACKFILL IS PROHIBITED (EXCEPT AS APPROVED BY THE
- FLOWABLE FILL IS PROHIBITED AS BACKFILL MATERIAL UNLESS OTHERWISE APPROVED BY CITY ENGINEER. WHEN APPROVED, SURFACE FINISHES MUST STILL BE MATCHED.

UTILITY INSTALLATION TRENCH DETAIL



(435) 654-2226

FEBRUARY 2019 N.T.S

75 NORTH MAIN STREET HEBER CITY, UTAH 84032 (435) 654-0757



HEBER CITY STANDARD DRAWING

GRANULAR BACKFILL MATERIAL COMPACTED TO 95%

MARKER TAPE 2' ABOVE PIPE

TRACER WIRE

NEW UTILITY LINE

UTILITIES-1